

TECHNICAL DATA SHEET

TDS 030			
Revision:	Date:	Page:	
10	06/19/2020	1/1	

RESCOL 65

Pine oil composed of a mixture of terpene alcohols and terpene hydrocarbons.

VERIFICATIONS					
Characteristics	UN	Specification / Tolerance	Method		
Total Terpene Alcohols (% by GC)	%	65 min.	ML SC 020		
Appearance	-	Yellowish transparent liquid	Visual		
Odor	-	Pine characteristic	ML SC 056		
Acid Number	mhKOH/g	2.0 max	ML SC 003		
Humidity	%	0.5 max	ML SC 025		
Specific gravity (20/4°C)	g/cm³	0.911 – 0.917	ML SC 013		
Refractive Index (20°C)	-	1.479 – 1.483	ML SC 014		
*Alpha Terpineol (% by GC)	%	50 min.	ML SC 020		
*Flash Point (open cup)	°C	65	ML SC 023		
		10% to 190			
*Distillation Range	°C	50% to 202	ML SC 024		
		90% to 215			

^{*} The sporadic analyzed parameters above do not characterize the product and should be taken only as reference.

APPLICATIONS

- ✓ Solvent used as masking agent in the paint industry;
- ✓ Disinfectant agent;
- ✓ Vehicles in agro-veterinary products.

BENEFITS

- ✓ Odor masking agent;
- ✓ Disinfectant;
- ✓ Bactericidal activity.

PACKAGING				
Туре	Size	Shelf life		
Line steel drums	180 Kg	12 months		
DISCLAIMER				

To prevent accidents and environmental impacts, please check the product SDS.

We request our customers to test our products before using them on industrial scale. The user of our products bears the responsibility of determining their suitability for a particular application or formulation or determining that the products or their use do not infringe any intellectual property.

We do not assume any responsibility or warranty, expressed or implied, resulting from handling, usage and storage whether performed according to the instructions contained in this document, whether used alone or in combination with other products. The buyer assumes all responsibility and liability for loss or damage arising from the handling and use of our products, either alone or in combination with other products.